



## EX d cable glands for non-armoured cables, OSNJ, brass nickel-plated, metric



OSNJ

**Marking:****Approval:****Protection class:****Temperature range:****Material:**

II 2 GD EEX d IIC/EEEx e II

IECEX KOS 09.0017X

NEMKO 03 ATEX 1460 X

IP 67

-20 °C - 120 °C

Brass nickel-plated, Gasket: Silicone

Type	WISKA-No. Ni					
OSNJ A2F-16a	50065500	M 16x1,5	15	3 - 7,5	24	1
OSNJ A2F-16b	50065501	M 16x1,5	15	6,1 - 10	24	1
OSNJ A2F-20a	50065502	M 20x1,5	15	10 - 13	27	1
OSNJ A2F-20b	50065503	M 20x1,5	15	13,1 - 15	27	1
OSNJ A2F-25a	50065504	M 25x1,5	15	14 - 17,5	32	1
OSNJ A2F-25b	50065505	M 25x1,5	15	16,1 - 19,5	32	1
OSNJ A2F-32a	50065506	M 32x1,5	15	18,1 - 22	39	1
OSNJ A2F-32b	50065507	M 32x1,5	15	21 - 26	39	1
OSNJ A2F-40a	50065508	M 40x1,5	15	24 - 28	48	1
OSNJ A2F-40b	50065509	M 40x1,5	15	27 - 32	48	1
OSNJ A2F-50a	50065510	M 50x1,5	15	32,1 - 34	58	1
OSNJ A2F-50b	50065511	M 50x1,5	15	34,1 - 40	58	1
OSNJ A2F-63a	50065512	M 63x1,5	15	38 - 44	73	1
OSNJ A2F-63b	50065513	M 63x1,5	15	43 - 50	73	1
OSNJ A2F-63c	50065514	M 63x1,5	15	49 - 54	73	1
OSNJ A2F-75a	50065515	M 75x1,5	15	52 - 56	85	1
OSNJ A2F-75b	50065516	M 75x1,5	15	55 - 60	85	1
OSNJ A2F-75c	50065517	M 75x1,5	15	59 - 62	85	1
OSNJ A2F-75d	50065518	M 75x1,5	15	62,1 - 66	85	1