

EX d Cable gland for non-armoured cables,
 OS-A2F-U, brass nickel-plated, metric


Marking Ex eb, Ex tbEx db
Approval IECEx, ATEX
Protection class IP66 / IP67
Temperature range -60 °C - 110 °C

Material

Gland Brass nickel-plated,
 Gasket Silicone



Type	Order No.	Threat	Ø Cable in mm	PU
OS-A2F-U 16 / M16	50107568	M 16x1,5	3 - 7	1
OS-A2F-U 16X / M16	50107569	M 16x1,5	5 - 10,3	1
OS-A2F-U 16X / M20	50108019	M 20x1,5	5 - 10,3	1
OS-A2F-U 20 / M20	50107570	M 20x1,5	9 - 15,3	1
OS-A2F-U 25 / M25	50107571	M 25x1,5	13 - 20	1
OS-A2F-U 32 / M32	50107572	M 25x1,5	17 - 26,5	1
OS-A2F-U 40 / M40	50107573	M 40x1,5	22 - 32	1
OS-A2F-U 50 / M50	50107574	M 50x1,5	30 - 42	1
OS-A2F-U 63 / M63	50107575	M 63x1,5	39 - 51	1
OS-A2F-U 63X / M63	50107576	M 63x1,5	46 - 55	1
OS-A2F-U 75 / M75	50107577	M 75x1,5	54 - 61	1
OS-A2F-U 75X / M75	50107578	M 75x1,5	58 - 68	1